

Micro Endoscopic Video System

Best Electronic Upgrade Solution for the Traditional Fiberscope





HD Imaging with Rich Detail



High-performance image sensor and ISP technology effectively reduce Moire Effect to ensure the best image quality.

Lighter, Flexible, and Wireless



The highly integrated & light weight design ensures delicate structure and attractive appearance.

Rotatable Display, Easy to Observe



The LCD screen can be rotated up to 120° degrees to allow you to always have the best angle of observation.

Large Storage with Eco-friendly Battery





Long-term storage for images and videos with great battery life.

	Main Parameters
Model	EV35R
Optical Adapter	C-Mount
Display Screen	3.5", 480*RGB*800
Tilt Range	0°~120°
Image Sensor	2 Million pixel high performance sensor
Image Format	JPG
Video Format	1080P, Mov
White Balance	AWB
Gain	AGC
Exposure	AE
Storage Medium	Maximum to 32GB
External Power Supply	AC100~240V 50/60Hz DC5V
Battery Capacity	Rechargeable and Removable Li-ion Battery (1,900mAh 3.7v)
Operating Time	Exceed 4 hrs
Net Weight	210±10g



North-Southern Electronics Limited

ADD:1F & 2F, Qiming Bldg., No.5 Tianfeng Rd., Science City, Guangzhou, 510530, CHINA TEL:+86 20 66343181 FAX:+86 20 66343180 Email: export@nsechina.com http://www.NSEChina.com





